

KX-TD7896 / KX-TD7896-W

2.4GHz Digital Frequency Hopping Spread Spectrum (FHSS)

Multi-Line Wireless Telephone

- 12 CO Line Capability
- 6-Line Multi-Function Backlit LCD Readout
- Speakerphone with Auto Answer
- Caller ID Compatible¹
- Headset Jack & Belt Clip
- Message Waiting Indicator
- Vibrating or Ringer Signal



2.4GHz
GIGARANGE



DIGITAL
SS **SPREAD**
SPECTRUM

Panasonic
ideas for life

KX-TD7896 2.4GHz Digital Frequency Hopping Spread Spectrum (FHSS) Multi-Line Wireless Systems Telephone with Backlit LCD Display

Enjoy the convenience of advanced system features, even when you're on the go

The KX-TD7896 proprietary multi-line wireless phone gives you the mobility, clarity and security of 2.4GHz Frequency Hopping Spread Spectrum (FHSS) operation, plus the functionality of a powerful system phone. Just clip the compact handset to your belt or purse and you're ready to receive or make calls from anywhere within range. An essential communications tool for both busy offices and homes, the KX-TD7896 can accommodate as many as 12 CO lines. It also possesses a host of sophisticated features that you can control with the handset's joystick and function buttons.

Outstanding Features with Built-In Quality

2.4GHz

Provides clear sound, enhanced range and reduced interference from radios, computer monitors and fluorescent lighting compared to ordinary wireless phones.

Frequency Hopping Spread Spectrum (FHSS) Technology

The Panasonic KX-TD7896 cordless phone utilizes Frequency Hopping Spread Spectrum (FHSS) technology in the 2.4GHz band. FHSS technology brings an important benefit to the user: security. Cordless phones with FHSS are more secure than regular cordless phones because they transmit over the entire bandwidth, constantly changing frequency. This constant change or Frequency Hopping deters electronic eavesdropping.

Hands-Free Speakerphone with Auto Answer

The convenient built-in speakerphone, combined with the Auto Answer feature, gives you the freedom to answer and talk hands free from anywhere within the converge area.

Joystick Navigation Key

This fast and reliable joystick can be used to adjust the handset, speaker and ringer volumes as well as to adjust the contrast of the LCD. Searching through the speed dial and accessing menu options has never been easier or quicker.

Caller ID Compatible¹

The KX-TD7896 can display an incoming caller's phone number or name for effective call screening.

Ringer Modes

The KX-TD7896 features 9 different ring melodies and 6 ring patterns to choose from. The vibrator ring is perfect for use in situations when an audible ring would not be desirable.

6-Line Multi-Function Backlit LCD Readout

Provides helpful information like Caller ID¹ data, call information, line status, and flexible key number or name.

Hands-Free Headset Jack

Now there's no need to interrupt your workflow just to answer the phone. You can connect an optional hands-free headset to the KX-TD7896 for automatic answering of intercom calls, plus access to features like BGM and Paging.

Wall-Mountable Base Antenna

You can keep the handset charger cradle on your desk and position the base antenna in a location that is central to your workspace, enabling you to maximize your range within that space.

High Capacity, Quick-Charging NiMH Battery

Convenient Belt Clip

Message Waiting Indicator

Out of Range Indication

7-Day Standby Time; 7-Hour Talk Time

Lighted Dial Keypad

Available in Black or Pearl White

KX-TD7896 Specifications	
Portable Handset	
Number of CO Lines	12
Flexible Key Labeling	Up to 12 Characters for Each Key
Speed Dial Memory	200 24 Digit Numbers
Call Log Outgoing	10 Numbers
Call Log Incoming	10 Numbers
Power Source	Ni-MH 650mAh
Language	English, French, Spanish
Ringer Modes	
Patterns	6
Melody	9
LED Patterns	4 Blinking Patterns
Vibration	7 Patterns
LCD	16 Characters / 6 Lines and Picture with a Backlight (Blue)
LCD Contrast	5 Levels
Charging Time	7 Hours
Talk Time	10 Hours
Standby Time	250 Hours
Available colors	Black or Pearl White
Dimensions (L x W x D)	5.6" x 0.6" x 0.57" Excluding Antenna Projection
Weight	5.2 oz.
Portable Handset Charger Base	
Power Source	AC Adaptor 120VAC 60Hz
Weight	4.0 oz.
Dimensions (L x W x D)	3.5" x 2.3" x 3.25"
Base Unit	
Power Source	AC Adaptor 120VAC 60Hz
Mounting Options	Wall or Desk
Weight	10.0 oz.
Dimensions (L x W x D)	7.7" x 1.5" x 5.25"

¹ Requires the installation of an optional Caller ID Card in the host Panasonic telephone system. Also requires a subscription to Caller ID service offered by certain telephone companies for a fee.

Panasonic ideas for life

Panasonic Consumer Electronics Company
Division of Panasonic Corporation of North America

Executive Offices: One Panasonic Way,
Secaucus, NJ 07094
(201) 348-7000
www.panasonic.com/csd

Panasonic Puerto Rico, Inc.

San Gabriel Industrial Park,
Ave. 65 de Infanteria, Km. 9.5,
Carolina, PR 00985
(787) 750-4300

Panasonic Customer Service

9am - 9pm (EST) Monday through Friday
10am - 7pm (EST) Saturday and Sunday
1-800-211-PANA
www.panasonic.com/support